

JIS G 3459 配管用ステンレス鋼鋼管 重量表 JIS G 3459 表8 抜粋

溶接鋼管

呼び径		外径 mm	呼び厚さ スケジュール5S		呼び厚さ スケジュール10S		呼び厚さ スケジュール20S		呼び厚さ スケジュール40		呼び厚さ スケジュール80	
A	B		厚さ mm	単位質量 kg/m	厚さ mm	単位質量 kg/m	厚さ mm	単位質量 kg/m	厚さ mm	単位質量 kg/m	厚さ mm	単位質量 kg/m
6	1/8	10.5	1.0	0.237 0.238	1.2	0.278 0.280	1.5	0.336 0.338	(2.0)	0.423 0.426	(2.5)	0.498 0.501
8	1/4	13.8	1.2	0.377 0.379	(1.5)	0.460 0.463	2.0	0.588 0.592	(2.5)	0.704 0.708	3.0	0.807 0.812
10	3/8	17.3	1.2	0.481 0.484	(2.0)	0.762 0.767	2.0	0.762 0.767	(2.5)	0.922 0.928	(3.5)	1.20 1.21
15	1/2	21.7	(1.5)	0.755 0.760	(2.0)	0.981 0.988	2.5	1.20 1.20	(3.0)	1.40 1.41	(3.5)	1.59 1.60
20	3/4	27.2	(1.5)	0.960 0.966	(2.0)	1.26 1.26	2.5	1.54 1.55	(3.0)	1.81 1.82	(4.0)	2.31 2.33
25	1	34.0	(2.0)	1.59 1.60	(2.5)	1.96 1.97	3.0	2.32 2.33	(3.5)	2.66 2.68	4.5	3.31 3.33
32	1 1/4	42.7	(2.0)	2.03 2.04	(3.0)	2.97 2.99	3.0	2.97 2.99	(3.5)	3.42 3.44	(5.0)	4.70 4.73
40	1 1/2	48.6	(2.0)	2.32 2.34	(3.0)	3.41 3.43	3.0	3.41 3.43	(4.0)	4.44 4.47	(5.0)	5.43 5.47
50	2	60.5	(2.0)	2.91 2.93	(3.0)	4.30 4.32	3.5	4.97 5.00	(4.0)	5.63 5.67	5.5	7.54 7.58
65	2 1/2	76.3	(2.0)	3.70 3.73	3.0	5.48 5.51	3.5	6.35 6.39	(5.0)	8.88 8.94	7.0	12.1 12.2
80	3	89.1	(2.0)	4.34 4.37	3.0	6.43 6.48	4.0	8.48 8.53	5.5	11.5 11.5	(8.0)	16.2 16.3
90	3 1/2	101.6	(2.5)	6.17 6.21	3.0	7.37 7.42	4.0	9.72 9.79	(6.0)	14.3 14.4	(8.0)	18.7 18.8
100	4	114.3	(2.5)	6.69 7.01	3.0	8.32 8.37	4.0	11.0 11.1	6.0	16.2 16.3	(9.0)	23.6 23.8
125	5	139.8	(3.0)	10.2 10.3	(3.5)	11.9 12.0	5.0	16.8 16.9	(7.0)	23.2 23.3	(10.0)	32.3 32.5
150	6	165.2	(3.0)	12.1 12.2	(3.5)	14.1 14.2	5.0	20.0 20.1	(7.0)	27.6 27.8	(12.0)	45.8 46.1
200	8	216.3	(3.0)	15.9 16.0	4.0	21.2 21.3	6.5	34.0 34.2	(8.0)	41.5 41.8	(13.0)	65.8 66.3
250	10	267.4	(3.5)	23.0 23.2	4.0	26.2 26.4	6.5	42.2 42.5	(10.0)	64.1 64.5	(15.0)	94.3 94.9
300	12	318.5	4.0	31.3 31.5	4.5	35.2 35.4	6.5	50.5 50.8	(10.0)	76.8 77.3	(18.0)	135 136

単位質量欄 上段= SUS304、SUS304L、SUS321 基本質量 7.93g/cm³のもの
下段= SUS316、SUS316L、SUS309S、SUS310S、SUS315J1、SUS317、SUS317L 基本質量 7.98g/cm³のもの