

純チタン丸棒 (JIS H4650)

TB340H

仕上	径 _(mm)	長さ _(mm)	質量 _(kg/M)
PM	10	× 4000	0.354
〃	12	× 4000	0.51
〃	13	× 4000	0.598
〃	14	× 4000	0.694
〃	15	× 4000	0.797
〃	16	× 4000	0.907
〃	18	× 4000	1.15
〃	20	× 4000	1.42
〃	22	× 4000	1.71
〃	25	× 4000	2.21
〃	28	× 4000	2.78
〃	30	× 4000	3.19
〃	32	× 4000	3.63
〃	35	× 4000	4.34
〃	38	× 4000	5.11
〃	40	× 4000	5.67
〃	42	× 4000	6.25
〃	45	× 4000	7.17
〃	50	× 4000	8.86
〃	55	× 4000	10.7
〃	60	× 4000	12.7
〃	65	× 4000	15.0
〃	70	× 4000	17.4
〃	75	× 4000	19.9
〃	80	× 4000	22.7
〃	85	× 4000	25.6
〃	90	× 4000	28.7
〃	95	× 4000	32.0
TM	100	× 4000	35.4
〃	110	× 3000	42.9
〃	120	× 3000	51.0
〃	130	× 3000	59.8
〃	140	× 3000	69.4
〃	150	× 3000	79.7
〃	160	× 3000	90.7
〃	170	× 1500	102
〃	180	× 1500	115

TB340H

仕上	径 _(mm)	長さ _(mm)	質量 _(kg/M)
TM	190	× 1500	128
〃	200	× 1500	142
〃	210	× 1500	156
〃	220	× 1500	171
〃	230	× 1500	187
〃	240	× 1500	204
〃	250	× 1500	221
〃	260	× 1500	239

PM: 圧延ピーリング品, TM: 鍛造ピーリング品

12
チタン
丸棒